



## SnowDogg™ HD75II Snow Plow

Buyers Part Number: HD75II

Buyers Products SnowDogg HD75 II Snow Plow has been re-imagined from the ground up starting with a floating A-frame™, increased ground clearance, and the all-new QuickMount II™.

- Corrosion-resistant 304 stainless steel moldboard with 3/8 in. cutting edge.
- Get an even scrape and even edge wear with the tubular steel Floating A-Frame™
- Enjoy 20% more ground clearance than previous HD models.
- Mount and dismount reliably and quickly with the all new QuickMount II™.
- Stack high, and lift fast with a municipal-style single chain lift arm.
- Fleet interchangeability with all prior HD, EX, TE, CM, and XP plows.
- Clear with speed and agility using the 70° attack angle and 1-1/2 inch angle cylinders.
- Fully enclosed 2 HP power/hydraulic unit with full size SAE standard cartridge valves, 3/8 in. rubber hoses, and integral valve manifold, or opt to use your truck's central hydraulics.
- Cut through the dark with powerful dual-beam halogen plow lights with secure double post mounts.
- Ergonomic, backlit control is easy to use with gloves on.
- Get the value you deserve with standard shock kit, cast shoes, snow deflector, and blade guides.



## Specifications

Angle Cylinders	1 1/2 x 12"	Angled Blade Width	78.0"
Blade Height	29"	Blade Width	90"

## Specifications continued:

<b>Cutting Edge</b>	3/8 x 6"	<b>Electrical</b>	Headlamp Rated Replaceable Micro-ISO Relays
<b>Harnesses</b>	Separate Light and Hydraulic 4GA Power Wires	<b>Lift Cylinder</b>	2 x 6"
<b>Lights</b>	Dual Halogen Bulbs	<b>Moldboard Material</b>	304 Stainless Steel
<b>Moldboard Thickness</b>	12 Ga	<b>Mounting System</b>	QuickMount II™
<b>Plow Shoes</b>	Standard	<b>Plow Type</b>	Straight Blade
<b>Ribs</b>	9	<b>Snow Deflector</b>	Contoured Poly
<b>Stand</b>	Independent Swing Down Feet	<b>Trip Springs</b>	4
<b>Trip Style</b>	Full Trip	<b>Shipping Weight</b>	680 lb