



SnowDogg™ HD80 II Snow Plow

Buyers Part Number: HD80II

Buyers Products SnowDogg HD80 II Snow Plow has been re-imagined from the ground up starting with a floating A-frame™, increased ground clearance, and the all-new QuickMount II™.

- Corrosion-resistant 304 stainless steel moldboard with 3/8 in. cutting edge.
- Get an even scrape and even edge wear with the tubular steel Floating A-Frame™
- Enjoy 20% more ground clearance than previous HD models.
- Mount and dismount reliably and quickly with the all new QuickMount II™.
- Stack high and lift fast with a municipal-style single chain lift arm.
- Fleet interchangeability with all prior HD, EX, TE, CM, and XP plows.
- Clear with speed and agility using the 70° attack angle and 1-1/2 inch angle cylinders.
- Fully enclosed 2 HP power/hydraulic unit with full size SAE standard cartridge valves, 3/8 in. rubber hoses, and integral valve manifold, or opt to use your truck's central hydraulics.
- Cut through the dark with powerful dual-beam halogen plow lights on secure double post mounts.
- Ergonomic, backlit control is easy to use with gloves on.
- Get the value you deserve with standard shock kit, cast shoes, snow deflector, and blade guides.



Specifications

Angle Cylinders	1 1/2 x 12"	Angled Blade Width	88.3"
Blade Height	29"	Blade Width	96"

Specifications continued:

Cutting Edge	3/8 x 6"	Electrical	Headlamp Rated Replaceable Micro-ISO Relays
Harnesses	Separate Light and Hydraulic 4GA Power Wires	Lift Cylinder	2 x 6"
Lights	Dual Halogen Bulbs	Moldboard Material	304 Stainless Steel
Moldboard Thickness	12 Ga	Mounting System	QuickMount II™
Plow Shoes	Standard	Plow Type	Straight Blade
Ribs	9	Snow Deflector	Contoured Poly
Stand	Independent Swing Down Feet	Trip Springs	4
Trip Style	Full Trip	Shipping Weight	700 lb