

FLG22 MODEL



22k Gooseneck Low-Pro Equipment Trailer

OPTIONAL



Treated Pine Flooring

Diamond Plate Fenders

Self-Cleaning Dovetail

2021 FLG22

Iron Bull Goosenecks are some of the most rugged and longest lasting units in service today. Low-Pro, pierced frame design lowers the deck 3" providing a lower center of gravity, more stable cornering and a lower loading angle for equipment.



NOW STANDARD



12" I-Beam Neck and Risers

Spare Tire

Torque Tube

12" I-Beam Pierced Frame

Rub Rail and Stake Pockets

Safety Chains
36" X 3/8 G#70 (26,400 Lb)

2 5/16" Adjustable Coupler

Lockable Full Neck Width Box

33" Deck Height

Powdura Powder Coat and One Cure Primer

25"-36" Coupler Height

Radial Tires

Dual Oversized Stirrup Steps

Cambered Dexter Nev-R-Adjust Brakes

Under Frame Bridge

2 - 10k Drop-Leg Jacks

STANDARD FEATURES

12" I-Beam Frame and Neck (19 lbs/ft)
2 5/16" Adjustable Coupler
3" Structural Crossmembers
2.5 x 2.5 Front Bumper Rail
Lockable Full Neck Width Tool Box
Rub Rail, Stake Pockets & Pipe Spools
Standard Torque Tube & Underframe Bridge
Dexter HDSS Standard
2-10K Nev-R-Adjust Electric Brake Axles
Multi-leaf Slipper Spring Suspension
E-Z Lube Hubs
25" Gooseneck Box

8' Slide-in Ramps
2-10k Drop-Leg Jack
Treated Pine 2x6 Floor
4 Standard 3" D-Rings
Black Mod Wheels
235/80R16 Radial Tires
Lifetime LED Lighting
All Lighting DOT Approved
Molded Sealed Harness with Resistors
7-Way Receiver Female Plug with Adapter
Powdura Powder Coat & One Cure Primer

BUILD A QUOTE ONLINE AT NORSTARCOMPANY.COM

GRAB A BULL BY THE HORNS

2021 BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	20	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	6300
102	22	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	6600
102	24	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	6920
102	25	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7310
102	26	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7410
102	28	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7640
102	30	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7855
102	32	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8105
102	34	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8350
102	36	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8675
102	38	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8900
102	40	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	9200

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

Photos may include optional features.

OPTIONAL FEATURES

CODE	DESCRIPTION	CODE	DESCRIPTION
10HS2	2 - 10000 Lb Electric Over Hydraulic Disc Axles	K21	12" Crossmembers (per ft)
12ES2	2 - 12000 Lb Electric Brake Axles	H72	6' Spread Axles
12HS2	2 - 12000 Lb Electric Over Hydraulic Disc Brake Axles	D60	Deck Over Neck
15ES2	2 - 15000 Lb Electric Brake Axles	T42	Side Tool Box
15AS2	2 - 15000 Lb Air Ride Axles	E04	Rough Oak Floor (per ft)
10ES3	3 - 10000 Lb Electric Brake Axles	W91	Cold Weather Harness
10HS3	3 - 10000 Lb Electric Over Hydraulic Brake Axles	NXX	Additional D-Rings (ea.)
12ES3	3 - 12000 Lb Electric Brake Axles	U30	Weld On Ratchet Track Only (per ft)
12HS3	3 - 12000 Lb Electric Over Hydraulic Brake Axles	U32	Weld On Ratchets Every 5' (per ft)
D30	Rampage Ramps (2 - 40" Flip-Over Ramps with 5' Self Cleaning Dove)	U31	Weld On Track with Adjustable Ratchets Every 5' (ft)
D35	5' Self Cleaning Dove Tail with Slide-in Ramps	T06	14-Ply 235/85 Tire Upgrade (ea.)
D31	5' Self Cleaning Dove Tail with 2 Flip-Over Ramps	T21	17.5"x6.75" Tire Upgrade (ea.)
D32	5' Self Cleaning Dove Tail with 3. Flip-Over Ramps	U52	Winch Plate 1/2" (In Neck)
J56	2 - 12k Hydraulic Jacks	S01	Tube Rear Support Stands
J55	Drop-Leg Jack (2-Speed)		

2021 FLG22 Optional Features



Rampage Ramps



Triple Axle Configurations



2 - 12K Electric Brake Axles

MAIN PHONE NUMBER
903-784-8900

5500 FM 38N, BROOKSTON, TX 75421

DEALER HOTLINE
844-466-7782