

TH 83" HYDRAULIC QUICK TILT

STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

Deck Width: 83"	Deck Height: 24"	Axles: Tandem (2 x 5,200 lb.)	Choose the optional Blackwood Pro decking for added durability and grip when wet.
Length: 18' - 22'	Couplers: Bumper Pull & Pintle	Load Capacity: 7,300 - 7,600 lbs.	
GVWR: 10,000 lbs.	Weight: 2,400 - 2,700 lbs.	Tilt Angle: 10°	



Our front Ram Hydraulic powered system gives you additional stability and control over the precise up and down movement of the bed for additional ease of use and loading/unloading flexibility.

HYDRAULIC POWERED TILT DECK



Simplify brake maintenance with our Forward Self-Adjusting Brakes, engineered to self-adjust for optimal braking performance. This innovative system reduces downtime and ensures consistent stopping power.

FORWARD SELF-ADJUSTING BRAKES



Benefit from enhanced cargo securement with our standard full-length Rubrail and stake pockets. In addition to the built-in stake pockets, the Rubrail provides extra attachment points for securing your load. Customize your trailer further by adding optional D-rings.

CARGO CONTROL STANDARD



Our 30" Diamond plate knife edge tail makes it super-easy to load low clearance equipment like scissor lifts and fork lifts.

KNIFE EDGE TAIL