

# TILT TRAILER GUIDE



SINGLE AXLE TILT: (T1) | QUICK TILT: (TH)

CHANNEL TILTS: (T5), (TF), (TS), (T6), (T7) | HD TILTS: (TJ), (TK)

DECKOVER TILTS: (T8), (T9), (TD)



THE PROFESSIONAL GRADE STANDARD



Length	Axles	Est. Base Weight†
22'	2 x 7,000 lbs	4,320 lbs / 1,960 kg
26'	2 x 7,000 lbs	4,860 lbs / 2,204 kg
28'	2 x 7,000 lbs	5,140 lbs / 2,331 kg

† Weights are estimated for base trailer.  
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

## STANDARD FEATURES

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- Adjustable 2 5/16" Ball Bulldog Coupler
- Safety Chains
- 1 - Drop Leg Jack (10,000 lb.)
- 2 - Dexter E- Z lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Tool Tray & Lockable Toolbox In Tongue
- 8" x 10 lb. I-Beam Tongue
- 8" x 10 lb. I-Beam Main Frame
- 3" Channel Crossmembers 16" on Center
- 2 x 6 x 1/8" Square Tubing Outer Deck Frame
- 22' Tilt Portion w/ 15 Degree Tilt Pitch
- 2" Treated Pine Lumber Deck
- 96" Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- 12VDC Hydraulic Pump
- 2 - 3" x 16" Hyd. Cylinders
- 12' Control Cable
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- 110V Integrated Trickle Charger
- GN Option Equipped with 2 Jacks
- GN Equipped with Front Toolbox
- GN Equipped with Chain Holder
- 5 year Dexter Axle Warranty

## AVAILABLE OPTIONS

\* denotes a standard feature

### COUPLER OPTIONS

- BP 2 5/16" Adjustable (14,000 lb.)
- BP 2 5/16" Adjustable Rigid Mount (25,000 lb.)
- 3" Pintle Eye - Channel-mount (20,000 lb.)
- GN 2 5/16" Round (25,000 lb.) w/ Toolbox
- GN 2 5/16" Square (25,000 lb.) w/ Toolbox
- BP 2 5/16" Adj. Cplr w/HD 6 hole Chn Brkt (20k)

### AXLE OPTIONS

#### 7,000# (DEXTER)

- (2) Electric (Spring)\*
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

#### 7,000# W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

#### 8,000# OIL BATH AXLES, 235/80 LR-E TIRES (DEXTER)

- (2) Electric (Spring)

#### 8,000# OIL BATH W/215/75R17.5 LR-H SINGLES(DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

### 8,000# OIL BATH W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

### TAIL OPTIONS

- 22' Tilt\*

### OTHER OPTIONS

- Blackwood Pro Full Deck
- Blackwood Pro Outer Deck
- Upgrade to 8 Hole Channel Adjustable Coupler
- 1 Extra Pair Flushmount D-Rings on Steel Floor
- 1 Pair D-Rings
- 2 Hydraulic Monster Jacks™
- Light Bar w/4 Lights
- Power Up/Down & Gravity Down Upgrade
- 1 Pair Weld-On Strap Ratchets
- Under Frame Spare Tire & Mnt.(Not Comp.w/17.5 T/W)
- Spare Tire and Mount (BP) 215/75/R17.5
- Top Riser Toolbox
- ½ x ½ Square Traction Bars on Rear of Deck
- Monster Steps on Both Sides
- Solar Battery Charger
- Plate for Winch

### 6" Taller GN Riser

- Full Size Divided Toolbox Upgrade (BP Only)
- 9,990 G.V.W.R.
- Frame Bridge
- 12"oc Crossmembers
- Rough Oak Floor
- 2nd Jack (Bumper Pull)
- Under Frame Tie Down Flat
- 4" Ratchets every 4ft w/ Slide Track
- Mount Only for Spare Tire
- 102" Deck Width
- Scissor Lift w/Cylinder
- Spare Tire and Mount (Bumper Pull)
- Bulldog 2-speed Jacks (12,000 lb.)
- Spare Tire & Mount (Bumper Pull) G Rated
- Roller on Front of Deck for Winch Cable



# HD DECKOVER TILT (T9)

Lengths: 24' - 36'



**I 12" I-BEAM FRAME**

Length	Axles	Est. Base Weight†
24'	2 x 7,000 lbs	6,250 lbs / 2,835 kg
26'	2 x 7,000 lbs	6,322 lbs / 2,868 kg
28'	2 x 7,000 lbs	6,450 lbs / 2,926 kg
30'	2 x 7,000 lbs	6,750 lbs / 3,062 kg

† Weights are estimated for base trailer.  
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

## STANDARD FEATURES

- 15,680 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- GN 2 5/16" Ball Bulldog Coupler 25,000 lb
- Safety Chains
- 2 - Drop Leg Jack (10,000 lb.)
- 2 - Dexter E- Z lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Monster Steps on Both Sides
- 3" Channel Crossmembers 16" on Center
- 2 x 6 x 1/8" Square Tubing Outer Deck Frame
- 24' Tilt Portion w/ 17 Degree Tilt Pitch
- 2" Treated Pine Lumber Deck
- 12" x 14 lb. I-Beam Main Frame, Riser & Neck
- 5" x 10.5" Hyd. Cylinder w/ Scissor Lift
- 102" Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- 12VDC Hydraulic Pump
- 12' Control Cable
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- 110V Integrated Trickle Charger
- GN Option Equipped with 2 Jacks
- GN Equipped with Front Toolbox
- GN Equipped with Chain Holder
- 5 year Dexter Axle Warranty

## AVAILABLE OPTIONS

\* denotes a standard feature

### COUPLER OPTIONS

- GN 2 5/16" Round (25,000 lb.) w/ Toolbox
- BP 2 5/16" Adjustable Rigid Mount (25,000 lb.)
- 3" Pintle Eye - Face-mount (36,000 lb.)
- GN 2 5/16" Square (25,000 lb.) w/ Toolbox

### AXLE OPTIONS

#### 7,000# (DEXTER)

- (2) Electric (Spring)\*
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)
- (2) Surge Disc [Surge Coupler] (Spring)
- (2) Surge Hydraulic Drum [Surge Coupler] (Spring)
- (3) Electric (Spring)
- (3) Electric (Torsion)
- (3) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)

#### 7,000# W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)
- (3) Electric (Spring)

#### 8,000# OIL BATH AXLES, 235/80 LR-E TIRES (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)

#### 8,000# OIL BATH W/215/75R17.5 LR-H SINGLES(DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)
- (3) Electric (Spring)

#### 8,000# OIL BATH W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Torsion)
- (3) Electric (Spring)

### TAIL OPTIONS

- 24' Tilt\*

### OTHER OPTIONS

- Blackwood Pro Full Deck
- Blackwood Pro Outer Deck
- 1 Extra Pair Flushmount D-Rings on Steel Floor
- 1 Pair D-Rings
- 2 Hydraulic Monster Jacks™
- Light Bar w/4 Lights
- Mud Flaps Single Wheel Deckover
- 1 Pair Weld-On Strap Ratchets
- 1 Side-mount Toolbox 30"x14"

- 1 Side-mount Toolbox 72"x14"
- 2 Extra Side Marker Lights, 1 Per Side
- Top Riser Toolbox
- 1/2 x 1/2 Square Traction Bars on Rear of Deck
- Solar Battery Charger
- Plate for Winch
- 6" Taller GN Riser
- Full Size Divided Toolbox Upgrade (BP Only)
- 9,990 G.V.W.R.
- Frame Bridge
- 12"oc Crossmembers
- Rough Oak Floor
- Under Frame Tie Down Flat
- 4" Ratchets every 4ft w/ Slide Track
- 11ga (3/4") DP Steel Floor w/ 4 D-Rings & 12"oc
- Bulldog 2-speed Jacks (12,000 lb.)
- Roller on Front of Deck for Winch Cable

# TANDEM DUAL TILT (TD)



Lengths: 24' - 40'



**I 12" I-BEAM FRAME**

Length	Axles	Est. Base Weight†
24'	2 x 10,000 lbs	7,580 lbs / 3,438 kg
28'	2 x 10,000 lbs	8,080 lbs / 3,665 kg
32'	2 x 10,000 lbs	8,580 lbs / 3,892 kg
36'	2 x 10,000 lbs	9,080 lbs / 4,119 kg
38'	2 x 10,000 lbs	9,330 lbs / 4,232 kg
40'	2 x 10,000 lbs	9,600 lbs / 4,354 kg

† Weights are estimated for base trailer.  
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

## STANDARD FEATURES

- 25,000 lb. G.V.W.R.
- 10,000 lb. x 2 G.A.W.R
- GN 2 5/16" Ball Bulldog Coupler 25,000 lb
- Safety Chains
- 2 - Dropleg Jacks (10,000 lb.)
- 2 - Dexter Oil Bath Axles (10,000 lb.)
- Torsion Suspension
- 8 Dual Wheels, 16" Grey, 8 on 6.5" Bolt Pattern
- 8 - 16" 235/80R16 Radial Tires (3,090 lb)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Monster Steps on Both Sides
- Lockable Front Toolbox w/Chain Holder
- Self-rising Bumper
- 24' Tilt Portion w/ 15 Degree Tilt Pitch
- 12VDC Hydraulic Pump
- Scissor Lift
- 12" x 19 lb. I-Beam Main Frame, Riser & Neck
- 8" x 15 lb. I-lb. Deck Frame
- 3" Channel Crossmembers 16" on Center
- 2 x 6 x 1/8" Square Tubing Outer Deck Frame
- Frame Bridging on 30' and Longer
- 2" Treated Pine Lumber Deck
- 102" Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- 110V Integrated Trickle Charger
- 5" x 17" Hyd. Cylinder w/Scissor Lift
- 10 year Dexter Torflex Axle Warranty

## AVAILABLE OPTIONS

\* denotes a standard feature

### COUPLER OPTIONS

- GN 2 5/16" Round (25,000 lb.) w/ Toolbox\*
- BP 2 5/16" Adj Rigid Mount (25,000 lb.) w/Tbx
- GN 2 5/16" Round (30,000 lb.) w/ 6" Longer Tube
- GN 2 5/16" Round (30,000 lb.) w/ Toolbox
- 3" Pintle Eye - Face-mount (36,000 lb.) w/Tbx
- GN 2 5/16" Square (30,000 lb.) w/ Toolbox
- GN 2 5/16" Square (25,000 lb.) w/ Toolbox

### AXLE OPTIONS

#### 10,000# W/235/75R17.5" LR-J SINGLE T&W (DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

#### 10,000# AXLES (DEXTER)

- (2) Electric (Air Ride)
- (2) Electric (Spring)
- (2) Electric (Torsion)\*
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Air Ride)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

#### 10,000# W/14 PLY LR-G DUAL T&W(DEXTER)

- (2) Electric (Spring)
- (2) Electric (Torsion)

#### 12,000# AXLES (DEXTER)

- (2) Electric (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Air Ride)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

#### 12,000# W/14 PLY LR-G DUAL T&W (DEXTER)

- (2) Electric (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

### TAIL OPTIONS

- 24' Tilt Deck

### OTHER OPTIONS

- Blackwood Pro Full Deck
- Blackwood Pro Outer Deck
- 1 Extra Pair Flushmount D-Rings on Steel Floor
- 1 Pair D-Rings
- HD 25k Jost 2x Jacks
- 2 Hydraulic Monster Jacks™
- Light Bar w/4 Lights
- 1 Pair Weld-On Strap Ratchets
- 1 Side-mount Toolbox 45"x17 1/2"
- 1 Side-mount Toolbox 72"x17 1/2"
- Solar Battery Charger
- Top Riser Toolbox

- 1/2 x 1/2 Square Traction Bars on Rear of Deck
- Hutch susp. H9700-Underslung Tandem Axle
- Plate for Winch
- 6" Taller GN Riser
- Under Frame Tie Down Flat
- 22 lb. I-Beam Main Frame, Riser & Neck
- 12"oc Crossmembers
- Rough Oak Floor
- 11ga (5/16") DP Steel Floor w/ 4 D-Rings & 12"oc
- Frame Bridging
- Bulldog 2-speed Jacks (12,000 lb.)
- Roller on Front of Deck for Winch Cable

# TILT OPTIONS GUIDE

## POWDER COAT COLOR OPTIONS:

ACTUAL COLOR MAY VARY, CHECK SPECIFIC MODEL PAGE FOR AVAILABLE COLORS



BLACK



GREY



DESERT TAN



WHITE



RED



TRACTOR ORANGE

## COUPLER OPTIONS:



BP 2 5/16" ADJ. CPLR W/HD 6 HOLE CHN BRKT (20K)



3" PINTLE EYE



8" I-BEAM GOOSENECK

## OTHER OPTIONS:



ROUGH OAK FLOOR



RUBRAIL




WINCH 12VDC (12,000 LB)



REMOVABLE DECK ON THE NECK



SPARE TIRE MOUNT



STEEL FLOOR & 4 D-RINGS



1 PAIR D-RINGS



WINCH CABLE ROLLER



12" ON-CENTER CROSSMEMBERS



SLIDING STRAP RATCHETS



WELD ON STRAP RATCHETS




SIDE-MOUNT TOOLBOX



2 SPEED JACKS



WINCH PLATE



SOLAR CHARGER



FULL SIZE DIVIDED TOOLBOX UPGRADE (T8 & T9)



TRAILER WINCH (9.5K - 17.5K)



1X1 ANGLE TRACTION BARS ON REAR OF DECK (T8, T9 & TD)



PALLET FORK HOLDERS (T6 & TF)

SOME OPTIONS NOT SHOWN, PLEASE VIEW PRODUCT PAGE FOR A LIST OF ALL OPTIONS



## PJ TRAILERS

- #1 Professional Grade Open Trailer Manufacturer
- Broad Line of Dumps, Flatdecks, Utilities, Carhaulers, Tilts & Equipment Trailers
- Over 300 Independent PJ Trailers Dealer Locations in the US & Canada

Visit Us Online at [www.pjtrailers.com](http://www.pjtrailers.com)



YouTube

Product Code	Trailer Model	GVWR	Deck Length	Deck Height	Deck Width*	Width Inside Fenders	Axle Sizes (lbs)	Std. Tire Size
<b>CAR HAULERS &amp; EQUIPMENT</b>								
B5	5" Channel Buggy Hauler	7,000 lbs.	16 - 22'	22" - 24"	102"	83"	Tandem (2 x 3,500-5,200 lbs. Axles)	ST205/75R15
B6	6" Channel Super-Wide	7,000 lbs.	18 - 24'	26"	102"	81"	Tandem (2 x 7,000 lb Axles)	ST235/80R16
B8	8" Channel Super-Wide	9,899 lbs.	20 - 40'	28"	102"		Tandem (2 x 7,000 lb Axles)	ST235/80R16
C4	4" Channel Carhauler	14,000 - 24,000 lbs.	14 - 20'	21"	83"	83"	Tandem (2 x 3,500 lbs. Axle)	ST205/75R15
C5	5" Channel Carhauler	14,000 - 24,000 lbs.	16 - 22'	21"	83"	83"	Tandem (2 x 3,500 lbs. Axle)	ST205/75R15
C8	8" Channel Equipment	7,000 - 10,400 lbs.	18 - 40'	27"	83"	83"	Tandem (2 x 7-8,000 lbs. Axle)	ST235/80R16
CC	6" Channel Equipment	14,000 - 16,000 lbs.	14 - 24'	25"	83"	83"	Tandem (2/3 x 5,200-8,000 lbs. Axle)	ST235/80R16
CE	5" Channel Carhauler	14,000 - 16,500 lbs.	16 - 22'	22"	83"	83"	Tandem (2 x 5,200 lbs. Axle)	ST225/75R15
H4	8" Pro-Beam™ Equipment	14,000 - 24,000 lbs.	20 - 28'	28"	82"	82"	Tandem (2 x 8,000 lbs. Axle)	ST235/80R16
H5	10" Pro-Beam™ Equipment	16,000 - 18,500 lbs.	20 - 32'	28"	82"	82"	Tandem (2 x 10,000 lbs. Axle)	ST235/75/R17.5
H6	8" Pro-Beam™ Super-Wide Equipment	20,000 - 23,000 lbs.	20 - 30'	28"	102"	82"	Tandem (2 x 8,000 Axle)	ST235/80R16
H7	10" Pro-Beam™ Super-Wide Equipment	16,000 - 18,500 lbs.	20 - 32'	28"	102"	82"	Tandem (2 x 10,000 Axle)	ST235/75/R17.5
P8	Angle Pipetop Trailer	20,000 - 23,000 lbs.	16 - 26'	23"	83"	83"	Tandem (2 x 3,500 lb Axles)	ST235/80R16
<b>DUMPS</b>								
D5	60" Utility Dump	5,200 - 9,990 lbs.	8' - 10'	26"		60"	Single & Tandem (1/2 x 3,500 - 7,000 lbs. Axles)	ST225/75R15
D3	72" Tandem Axle Dump	9,990 - 9,990 lbs.	10 - 12'	28"		72"	Tandem (2 x 3,500 - 7,000 lbs. Axles)	ST225/75R15
DE	HD Low-Pro Dump	20,000 lbs.	16'	26"		82.5"	Tandem (2 x 10,000 lbs. Axles)	ST235/75/R17.5
DL	83" Low-Pro Dump	14,000 - 16,000 lbs.	12 - 16'	24"		83"	Tandem (2 x 7,000 - 8,000 lbs. Axles)	ST235/80R16
DM	83" Low-Pro High Side Dump	14,000 - 16,000 lbs.	12 - 16'	24"		83"	Tandem (2 x 7,000 lb. Axles)	ST235/80R16
D8	96" Deckover Dump	14,000 - 16,000 lbs.	14 - 16'	34"		96"	Tandem (2 x 7-8,000 lbs. Axle)	ST235/80R16
DD	Tandem Dual Dump	25,000 - 28,000 lbs.	16 - 20'	39"		96"	Tandem & Triple (2 x 10-12,000 lbs. Axle)	ST235/80R16
DR	Roll-Off Dump	14,000 - 15,680 lbs.	14 - 14'	32"		83"	Tandem (2 x 7,000 lbs. Axle)	ST235/80R16
<b>FLATDECKS &amp; DECKOVERS</b>								
LS	Low-Pro Flatdeck With Singles	15,680 - 24,000 lbs.	20 - 40'	33"	102"		Tandem & Triple (2/3 7-8,000 lbs. Axles)	ST235/80R16
LD	Low-Pro Flatdeck With Duals	25,000 - 30,000 lbs.	20 - 44'	33"	102"		Tandem & Triple (2/3 10-15,000 lbs. Axles)	ST235/80R16
L3	14" I-Beam Low-Pro With Duals	30,000 lbs.	20 - 42'	36"	102"		Tandem & Triple (2/3 x 10-15,000 lbs. Axles)	ST235/80R16
LY	Low-Pro With Hydraulic Dove	25,000 - 36,000 lbs.	30 - 44'	33"	102"		Tandem & Triple (2/3 x 10-15,000 lbs. Axles)	ST235/80R16
L6	Medium Duty Deckover 6" Channel	9,990 lbs.	14 - 24'	33"	101"		Tandem (5,200 lbs. Axles)	ST225/75R15
F8	8" I-Beam Deckover	9,900 - 16,000 lbs.	16 - 30'	33"	96-102"		Tandem & Triple (5,200 - 8,000 lbs. Axles)	ST235/80R16
PL	Low-Pro Pintle With Duals	25,000 - 36,000 lbs.	20 - 44'	33"	102"		Tandem & Triple (2/3 10-15,000 lbs. Axles)	ST235/80R16
<b>TILTS</b>								
TS	6" Channel Super-Wide Tilt	14,000 - 15,680 lbs.	18 - 24'	21-1/2"	102"	81"	Tandem (2 x 7,000 lb. Axles)	ST235/80R16
T1	Single Axle HD Tilt	5,200 - 7,000 lbs.	13 - 16'	19" - 21"	81"	81"	Single (5,200 - 7,000 lbs. Axles)	ST235/80R16
TH	Hydraulic Quick Tilt	7,000 - 9,900 lbs.	16 - 22'	24"	83"	83"	Tandem (2 x 3,500 - 5,200 lbs. Axles)	ST205/75R15
T5	5" Channel Tilt Carhauler	7,000 - 9,900 lbs.	16 - 22'	24"	83"	83"	Tandem (2 x 3,500 - 5,200 lbs. Axles)	ST205/75R15
TF	Powered Full Tilt	9,900 - 24,000 lbs.	18 - 24'	22"	83"	82"	Tandem & Triple (2/3 x 5,200 - 7,000 lbs. Axles)	ST235/80R16
T6	6" Channel Equipment Tilt	14,000 - 15,680 lbs.	16 - 24'	21"	83"	82"	Tandem (2/3 x 7,000 lbs. Axles)	ST235/80R16
T7	8" Channel Tilt	14,000 - 24,000 lbs.	16 - 40'	24"	83"	82"	Tandem & Triple (2/3 x 5,200 - 7,000 lbs. Axles)	ST235/80R16
TJ	HD Equipment Tilt 6" Channel	14,000 - 16,000 lbs.	16 - 24'	23"	82"	82"	Tandem (2 x 7,000 - 8,000 lbs. Axles)	ST235/80R16
TK	HD Equipment Tilt 8" Channel	14,000 - 24,000 lbs.	16 - 40'	23"	82"	82"	Tandem & Triple (2/3 x 7 - 8,000 lbs. Axles)	ST235/80R16
T8	Deckover Tilt	14,000 - 16,500 lbs.	22 - 28'		96" -		Tandem & Triple (2 x 7 - 8,000 lbs. Axles)	ST235/80R16
T9	HD Deckover Tilt	15,680 - 24,000 lbs.	24 - 36'	36"	102"		Tandem & Triple (2/3 x 7 - 8,000 lbs. Axles)	ST235/80R16
TD	Tandem Dual Tilt	25,000 - 28,000 lbs.	24 - 40'		102"		Tandem (2 x 10,000 lbs. Axles)	ST235/80R16
<b>UTILITIES</b>								
U6	60" Single Axle Channel Utility	2,990 - 4,995 lbs.	8' - 14'	21"	60"	60"	Single (3,500 - 5,200 lb Axle)	ST205/75R15
U2	72" Single Axle Channel Utility	2,990 - 4,995 lbs.	8' - 14'	21"	72"	72"	Single (3,500 - 5,200 lb Axle)	ST205/75R15
U7	77" Single Axle Channel Utility	2,990 - 4,995 lbs.	8' - 14'	21"	77"	77"	Single (3,500 - 5,200 lb Axle)	ST205/75R15
U8	83" Single Axle Channel Utility	2,990 - 4,995 lbs.	8' - 14'	21"	83"	83"	Single (3,500 - 5,200 lb Axle)	ST205/75R15
UC	60" Tandem Axle Channel Utility	7,000 - 9,899 lbs.	10 - 14'	21"	60"	60"	Tandem (2 x 3,500 - 5,200 lb. Axles)	ST205/75R15
UJ	72" Tandem Axle Channel Utility	7,000 - 9,899 lbs.	10 - 22'	21"	72"	72"	Tandem (2 x 3,500 - 5,200 lb. Axles)	ST205/75R15
UK	77" Tandem Axle Channel Utility	7,000 - 9,899 lbs.	10 - 22'	21"	77"	77"	Tandem (2 x 3,500 - 5,200 lb. Axles)	ST205/75R15
UL	83" Tandem Axle Channel Utility	7,000 - 9,899 lbs.	10 - 22'	21"	83"	83"	Tandem (2 x 3,500 - 5,200 lb. Axles)	ST205/75R15

Please Note: Specifications subject to change without notice. Please contact PJ Trailers directly to verify specifications. All measurements may vary +/- 1"

\* Deck width measured from rub rail to rub rail where applicable.